

OMNISPOWER[®]
POWER THE FUTURE

CRYSTALLINE SOLAR PANEL

Part Number	OP550M72-P3
Maximum Power with tolerance(Pmax)	550W(0~3%)
Maximum Power Voltage(Vmp)	41.60V
Maximum Power Current(Imp)	13.23A
Open Circuit Voltage with tolerance(Voc)	49.80V
Short Circuit Current with tolerance(Isc)	13.99A
Fire Performance	Class C
Max Series Fuse Rating	30A
STC Test Conditions	1000W/m ² ,AM1.5,25°C
Maximum System Voltage	1500V(IEC)
Protection Class	II
Weight	28Kg
Dimension	2279x1134x35mm

*Measuring tolerance: ±3%.

⚠ WARNING ⚠ ELECTRICAL HAZARDS

Only qualified personnel should install or perform maintenance work on these modules.
This unit produces electricity if exposed to light.
Follow all applicable electrical safety precautions.
Don't disconnect when loading.
Don't damage or scratch the rear surface of the module

Omnis Power USA INC.

www.omnispower.com
info@omnispower.com
100N Howard ST STE R,Spokane,
Washington 99201 USA



Tested to IEC 61215: 2016
and IEC 61730: 2016

DESIGNED IN USA



OP352076S7566